

microui

User Manual



MICROEJ[®]

Reference:	TLT-XXX-MAN-microui-microui
Version:	4.0.0
Revision:	XXX

Confidentiality & Intellectual Property

All rights reserved. Information, technical data and tutorials contained in this document are confidential and proprietary under copyright Law of Industrial Smart Software Technology (IS2T S.A.) operating under the brand name MicroEJ®. Without written permission from IS2T S.A., *copying or sending parts of the document or the entire document by any means to third parties is not permitted*. Granted authorizations for using parts of the document or the entire document do not mean IS2T S.A. gives public full access rights.

The information contained herein is not warranted to be error-free. IS2T® and MicroEJ® and all relative logos are trademarks or registered trademarks of IS2T S.A. in France and other Countries.

Java™ is Sun Microsystems' trademark for a technology for developing application software and deploying it in cross-platform, networked environments. When it is used in this documentation without adding the ™ symbol, it includes implementations of the technology by companies other than Sun.

Java™, all Java-based marks and all related logos are trademarks or registered trademarks of Sun Microsystems Inc, in the United States and other Countries.

Other trademarks are proprietary of their authors.

Table of Contents

1. Data Structure Documentation	1
1.1. ui_rect_collection_t Struct Reference	1
1.1.1. Detailed Description	1
2. File Documentation	2
2.1. bsp/ui/src/LLUI_DISPLAY_HEAP_impl.c File Reference	2
2.1.1. Detailed Description	2
2.2. bsp/ui/src/LLUI_INPUT_LOG_impl.c File Reference	2
2.2.1. Detailed Description	3
2.3. bsp/ui/src/microui_event_decoder.c File Reference	3
2.3.1. Detailed Description	3
Index	4

Chapter 1. Data Structure Documentation

1.1. ui_rect_collection_t Struct Reference

Data Fields

- ui_rect_t [UI_RECT_COLLECTION_MAX_LENGTH]
- size_t

1.1.1. Detailed Description

Definition at line 45 of file ui_rect_collection.h.

The documentation for this struct was generated from the following file:
bsp/ui/inc/ui_rect_collection.h

Chapter 2. File Documentation

2.1. bsp/ui/src/LLUI_DISPLAY_HEAP_impl.c File Reference

This MicroUI images heap allocator replaces the default allocator embedded in the MicroUI Graphics Engine. It is using a best fit allocator and provides some additional APIs to retrieve the heap information: total space, free space, number of blocks allocated.

```
#include "microui_heap.h"
#include "BESTFIT_ALLOCATOR.h"
```

Macros

- #define (68)
- #define (block) ((*uint32_t*)((block)-sizeof(uint32_t))) & 0x7ffffff)

Functions

- uint32_t (void)
- uint32_t (void)
- uint32_t (void)
- void (uint8_t *heap_start, uint8_t *heap_limit)
- uint8_t * (uint32_t size)
- void (uint8_t *block)

2.1.1. Detailed Description

This MicroUI images heap allocator replaces the default allocator embedded in the MicroUI Graphics Engine. It is using a best fit allocator and provides some additional APIs to retrieve the heap information: total space, free space, number of blocks allocated.

See also. LLUI_DISPLAY_impl.h file comment

Author. MicroEJ Developer Team

Version. 4.0.0

Since. MicroEJ UI Pack 13.1.0

2.2. bsp/ui/src/LLUI_INPUT_LOG_impl.c File Reference

This MicroUI FIFO (queue) logger replaces the default logger embedded in the MicroUI Input Engine. For each queue event, it stores the event's data size. This allows to be able to decode the event when `LLUI_INPUT_dump()` is called.

```
#include <assert.h>
#include <string.h>
#include <LLUI_INPUT_impl.h>
#include "microui_event_decoder.h"
```

2.2.1. Detailed Description

This MicroUI FIFO (queue) logger replaces the default logger embedded in the MicroUI Input Engine. For each queue event, it stores the event's data size. This allows to be able to decode the event when `LLUI_INPUT_dump()` is called.

This logger does not interpret the event: it just recognizes the event's first element and event's data. When an event is detected, the logger calls `microui_event_decoder.h` functions.

See also. `LLUI_INPUT_impl.h` file comment

Author. MicroEJ Developer Team

Version. 4.0.0

Since. MicroEJ UI Pack 13.1.0

2.3. bsp/ui/src/microui_event_decoder.c File Reference

This MicroUI Events decoder describes the events to the standard output stream.

```
#include "microui_event_decoder.h"
```

2.3.1. Detailed Description

This MicroUI Events decoder describes the events to the standard output stream.

See also. `LLUI_INPUT_LOG_impl.c` file comment

Author. MicroEJ Developer Team

Version. 4.0.0

Since. MicroEJ UI Pack 13.1.0

Index

B

bsp/ui/src/LLUI_DISPLAY_HEAP_impl.c, 2

bsp/ui/src/LLUI_INPUT_LOG_impl.c, 2

bsp/ui/src/microui_event_decoder.c, 3

U

ui_rect_collection_t, 1